

Enhancing everyday living







ENGINEERING SUBMITTAL DATA SHEET

Commercial electric water heaters, Flexible

105 MODELS (Light & Medium Duty)


40 imperial gallons / 184 litres Insulated with 2" Eco-Friendly GREENFOAM

208, 240, 277 & 480 Volts / Single phase

These models meet the safety and construction requirements of CSA Standard C22.2 No. 110 and meet or exceed the standby loss requirements of NRCan and ASHRAE 90.1 Standard.

Models*	Input		Phase	Number			
	(kW)	208 Volts 240 Volts 277 Volts 480 Volts		480 Volts	1 11000	of elements	
Light & Medium Du	ity with 2	or 4 elements					
1052Y-1-3S	3	14.4	12.5	10.8	6.3		2
1052Y-1-4.5S	4.5	21.6	18.8	16.2	9.4		
1052Y-1-5S	5	24.0	20.8	18.1	10.4		
1052Y-1-6S	6	_	25.0	21.7	12.5		
1054Y-1-6S	6	28.8	25.0	21.7	12.5] '	
1054Y-1-9S	9	43.3	37.5	32.5	18.8		4
1054Y-1-10S	10	48.1	41.7	36.1	20.8	1	4
1054Y-1-12S	12	_	50.0	43.3	25.0		

^{*} Replace the "Y" by the letter referring to its voltage (refer to the following "Voltage index" as well as the "Model Number Structure" for further details).



	Voltage index								
Α	208 Volts								
В	240 Volts								
D	480 Volts								
Е	277 Volts								

Notes:			

See reverse for this model drawing as well as order details.








Commercial electric water heaters, Flexible

105 MODELS

(Light & Medium Duty)

40 imperial gallons / 184 litres



Models	Storage Capacity		Α	B C D		Е	F	G	Est. Ship. Weight			
Models	lmp. gal.	Litres	U.S. gal.	Inches (cm)	Inches (cm)	Inches (cm)	Inches (cm)	Inches (cm)	Inches (cm)	Inches (cm)	lb.	kg
All 105	40	184	49	3 1/8 (7.9)	40 3/16 (102.1)	49 1/8 (124.8)	4 7/8 (12.4)	50 3/4 (129)	26 1/4 (66.7)	22 (55.9)	230	104

Notes:			
IOD TITLE	QUANTITE DATE		
JOB TITLE	SUBMITTED DATE		
ADDRESS	REQUIRED PRODUCT		
	MODEL NO.	SIZE	QUANTITY
CONTRACTOR	MODEL NO.	SIZE	QUANTITY
ADDRESS	MODEL NO.	SIZE	QUANTITY
	MODEL NO.	SIZE	QUANTITY
ENGINEER	REQUIRED DATE		

 $In\ accordance\ with\ our\ company\ policy\ of\ on-going\ product\ improvement,\ Giant\ Factories\ Inc.\ reserves\ the\ right\ to\ make\ changes\ without\ prior\ notice.$





Enhancing everyday living







ENGINEERING SUBMITTAL DATA SHEET

Commercial electric water heaters, Flexible

105 MODELS (Heavy Duty)

40 imperial gallons / 184 litres

Insulated with 2" Eco-Friendly GREENFOAM


208, 240, 277 & 480 Volts

These models meet the safety and construction requirements of CSA Standard C22.2 No. 110 and meet or exceed the standby loss requirements of NRCan and ASHRAE 90.1 Standard.

Models*	Input		Amp		Phase(s)	Number		
	(kW)	208 Volts 240 Volts 277 Volts 480 Volts		480 Volts	1 11400(0)	of elements		
Heavy Duty with 3,	, 6, or 9 ele	ements						
1053Y-1-6S		28.8	25.0	21.7	12.5	1		
1053Y-3-6S	6	16.7	14.5	_	7.2	3		
1053Y-1-9S	9	43.3	37.5	32.5	18.8	1		
1053Y-3-9S	9	25.0	21.7	_	10.8	3		
1053Y-1-12S	10	57.7	50.0	43.3	25.0	1	2	
1053Y-3-12S	12	33.3	28.9	_	14.4	3	3	
1053Y-1-13.5S	13.5	64.9	56.3	48.7	28.1	1		
1053Y-3-13.5S	13.5	37.5	32.5	_	16.2	3		
1053Y-1-15S	15	72.1	62.5	54.2	31.3	1		
1053Y-3-15S	15	41.6	36.1	_	18.0	3		
105XY-1-18S	10	86.5 [†]	75.0	65.0	37.5	1	3 or 6	
105XY-3-18S	18	50.0 [†]	43.3	_	21.7	3	3 UI U	
1056Y-1-24S	24	115.4	100.0	86.6	50.0	1		
1056Y-3-24S	24	66.6	57.7	_	28.9	3		
1056Y-1-27S	27	129.8	112.5	97.5	56.3	1	6	
1056Y-3-27S	21	74.9	65.0	_	32.5	3	0	
1056Y-1-30S	30	144.2	125.0	108.3	62.5	1		
1056Y-3-30S	30	83.3	72.2	_	36.1	3		
105XY-1-36S	36	173.1 ^{††}	150.0	130.0	75.0	1	6 or 9	
105XY-3-36S	30	99.9 ^{††}	86.6	_	43.3	3	0 01 9	
1059Y-1-40.5S	40.5	194.7	168.8	146.2	84.4	1		
1059Y-3-40.5S	40.5	112.4	97.4	_	48.7	3		
1059Y-1-45S	45	216.3	187.5	162.5	93.8	1	9	
1059Y-3-45S	45	124.9	108.3	_	54.1	3	9	
1059Y-1-54S	- 54	_	255.0	194.9	112.5	1		
1059Y-3-54S] 54	_	129.9	_	65.0	3		

^{*} Replace the "X" in the model number by the element quantity shown in the "Number of elements" column as well as the "Y" by the letter referring to its voltage (refer to the following "Voltage index" as well as the "Model Number Structure" for further details).

^{††} For 208 V Models with a 36kW input, only the 9-element configuration is possible.



	Voltage index							
Α	208 Volts							
В	240 Volts							
D	480 Volts							
Е	277 Volts							

See reverse for this model drawing as well as order details.



In accordance with our company policy of on-going product improvement, Giant Factories Inc. reserves the right to make changes without prior notice.

[†] For 208 V Models with a 18 kW input, only the 6-element configuration is possible.




Commercial electric water heaters, Flexible

105 MODELS

(Heavy Duty)

40 imperial gallons / 184 litres



Models	Storage Capacity		Α	В	С	D	E	F	G	Est. Ship	. Weight	
Models	Imp. gal.	Litres	U.S. gal.	Inches (cm)	Inches (cm)	Inches (cm)	Inches (cm)	Inches (cm)	Inches (cm)	Inches (cm)	lb.	kg
All 105	40	184	49	3 1/8 (7.9)	40 3/16 (102.1)	49 1/8 (124.8)	4 7/8 (12.4)	50 3/4 (129)	26 1/4 (66.7)	22 (55.9)	230	104

Notes:			
JOB TITLE	SUBMITTED DATE		
ADDRESS	REQUIRED PRODUCT		
	MODEL NO.	SIZE	QUANTITY
CONTRACTOR	MODEL NO.	SIZE	QUANTITY
ADDRESS	MODEL NO.	SIZE	QUANTITY
	MODEL NO.	SIZE	QUANTITY
ENGINEER	REQUIRED DATE		

 $In\ accordance\ with\ our\ company\ policy\ of\ on-going\ product\ improvement,\ Giant\ Factories\ Inc.\ reserves\ the\ right\ to\ make\ changes\ without\ prior\ notice.$





Enhancing everyday living







ENGINEERING SUBMITTAL DATA SHEET

Commercial electric water heaters, Flexible

105 MODELS (Heavy Duty)


40 Imp. gallons / 184 litres

Insulated with 2" Eco-Friendly GREENFOAM

600 Volts / Three phases with 3, 6 or 9 elements

These models meet the safety and construction requirements of CSA Standard C22.2 No. 110 and meet or exceed the standby loss requirements of NRCan and ASHRAE 90.1 Standard.

Models	Input (kW)	Number of elements	Amperage
1053C-3-6S	6		5.8
1053C-3-9S	9		8.7
1053C-3-12S	12	3	11.5
1053C-3-13.5S	13.5	3	13.0
1053C-3-15S	15		14.4
1053C-3-18S	18		17.3
1056C-3-18S	18		17.3
1056C-3-24S	24		23.1
1056C-3-27S	27	6	26.0
1056C-3-30S	30		28.9
1056C-3-36S	36		34.6
1059C-3-36S	36		34.6
1059C-3-40.5S	40.5		39.0
1059C-3-45S	45	9	43.3
1059C-3-54S	54		52.0



Voltage Index 600 Volts

Notes:	 	 	

See reverse for this model drawing as well as order details.








Commercial electric water heaters, Flexible

105 MODELS (Heavy Duty)

40 Imp. gallons / 184 litres



Models	Storage Capacity		Α	В	С	D	E	F	G	Est. Ship	. Weight	
Models	Imp. gal.	Litres	U.S. gal.	Inches (cm)	Inches (cm)	Inches (cm)	Inches (cm)	Inches (cm)	Inches (cm)	Inches (cm)	lb.	kg
All 105	40	184	49	3 1/8 (7.9)	40 3/16 (102.1)	49 1/8 (124.8)	4 7/8 (12.4)	50 3/4 (129)	26 1/4 (66.7)	22 (55.9)	230	104

Notes :				
JOB TITLE	SUBMITTED DATE			
ADDRESS	REQUIRED PRODUCT	REQUIRED PRODUCT		
	MODEL NO.	SIZE	QUANTITY	
CONTRACTOR	MODEL NO.	SIZE	QUANTITY	
ADDRESS	MODEL NO.	SIZE	QUANTITY	
	MODEL NO.	SIZE	QUANTITY	
ENGINEER	REQUIRED DATE			

In accordance with our company policy of on-going product improvement, Giant Factories Inc. reserves the right to make changes without prior notice.

